



Versatile Linux Device

The robust platform of the IA7200 is CLI's latest unique, multipurpose desktop. Equipped with an on board 2.41GHz dual core Intel® Celeron® processor, this device provides performance while maintaining cool operating temperatures without the aid of a fan.

The IA7200 is offered on the Linux 64-bit operating system. This unit provides a budget friendly solution for your terminal emulation and VDI environments. CLI's IA7200 provides a secure locked down unit for connectivity to common virtualization platforms or as a thin client for broader functionality. With easy setup this desktop is truly plug and play. The IA7200 slim product profile saves on your desktop real estate via the included stand or mounted to the back of a monitor.

The IA7200 shines in the most complex VDI environments offering a superb user experience no matter how demanding the applications.

At a Glance

The IA7200, provides a robust Linux desktop solution with the versatility demanded in today's complex environments. At a cost competitive price point this unit provides the most flexibility while accommodating your budget. Simply put, this device presents the best of both worlds—delivering the ability to satisfy your desktop needs at an affordable price.

Features

- Intel® Celeron® 2.41GHz Dual Core Processor
- Dual Video Support with DVI and Display Port
- Image Update with USB Drive Supported
- Citrix HDX® Premium Verified
- Microsoft® RemoteFX® Certified
- VMware Horizon View® Ready
- Linux 64-bit OS
- Low Power Consumption



CLI IA7200 Universal Client

Modular Logic Unit, Intel® Celeron® J1800 Dual Core 2.41GHz, CPU. 1 Gigabit Ethernet Port, 5 USB 2.0 Ports, 1 USB 3.0 Port, Audio In/Out ports, External Power Supply, DRAM and Industrial Grade SSD Flash, Security Lock Slot, USB Optical Mouse, US Power Cord, One Year Return-To-Depot Warranty.

CONFIGURATION	DESCRIPTION		IA7200L
Operating System	Linux 64-bit Operating		Linux 64-bit
Processor	Intel® Celeron® J1800 Dual Core Processor 2.41GHz		
Video	Intel® HD Graphics DP/VGA: Up To 2560 x1600 Wide Screen Resolution @60Hz DVI-I: Up To 1920 x 1200 Wide Screen Resolution @60Hz 32-bit Color Extended Dual Screen Display Supported With Optional Display Port Cable, (1) DVI-I to VGA Adapter Included		
Flash	mSATA SSD Flash Module		16GB
Memory	DDR3L (1.35V) 1333MHz SDRAM Low Power		Min 2GB Max 4GB
Audio	2 Audio Jacks: (1) Line-Out, (1)Microphone In		
Communications	(1) Gigabit Ethernet Port		
Ports and Connectors	(1) USB 3.0 Port (Front), (5) USB 2.0 Ports (Rear), (1) DVI-I, (1) DP, (1) RJ45 Ethernet Port, (1) Mic-In Jack, (1) Audio Out Jack, (1) PCIe Mini PCIe Expansion Port (Not Available When Configured For Wireless)		
Mounting Hardware	Standard: VESA 100mm Compliant Mounting Holes (VESA Kit Included), Vertical Feet, Horizontal Feet		
Power Supply	Auto Sensing 100 – 240 VAC, 50/60Hz, Max 10 Watt		
Terminal Emulation	Optional Ericom PowerTerm®		
Protocols	Microsoft® RDC/RemoteFX®, Citrix ICA/HDX®, VMware Horizon View®, Web Browser, Telnet, TCP/IP with DNS, XDMCP, DHCP, and PPP		
Weight	1.35 lbs.		
Dimensions	(w x d x h) 1.24 x 5.16 x 6.57 inches		
Temperature & Humidity	Operating 0°C to 40°C, 30% to 80% Non-Condensing Humidity		
Safety Certifications	RoHS, FCC Class B, VCCI, UL, CE		
Warranty	Limited One Year Hardware Warranty		

CLI, Inc. 735 Challenger Street, Brea, CA 92821

info@computerlab.com | 1 714-572-8000 | www.computerlab.com

© 2015 CLI, Inc. All rights reserved. Specifications are subject to change without notice. CLI is a registered trademark. All other trademarks are the property of their respective owners. CLI shall not be liable for technical or editorial errors or omissions contained herein.

